


Always check our website for the most updated specifications: www.zumacollection.com



Pictured with optional waste and overflow

All bathtub dimensions are $\pm 1/2"$.

CODES AND COMPLIANCE

Products meet or exceed the following standards:

- Underwriters Laboratories (UL)
- Underwriters Laboratories - Canada (cUL)
- ANSI Z124.1 • ANSI A112-19.7
- ANSI A112.19.8

ELECTRICAL REQUIREMENTS

We recommend one 20 amp ground fault circuit interrupter (GFCI) for each power supply provided with the bathtub.

DIMENSIONS


66" x 44" x 23"

Whirlpool Operating Gallons: 66


Gallons to Overflow: 85

Material: Acrylic


Whirlpool



Combination (pump and blower location only)



Airbath System II



OPTIONAL ACCESSORIES

- Chromotherapy Light
- Grab Bars
- High Density Insulation
- iBath Sound System
- Ozone System
(Whirlpool and/or Airbath only)
- Pillow -12"
- Rotary Jets
- Thermal Comfort System
(TCS must be at opposite end if used with VSM)
- Vibro Sonic Massage
(VSM must be at opposite end if used with TCS)
- Waste & Overflow
- Linear Overflow

SUCTION	SYLLENT PUMP	BLOWER	JET	ON/OFF CONTROL
	ACCESS PANEL (MINIMUM 16" X 20")			

Undermount Yes No

INSTALLATION TIPS

- Install product according to Owners manual and local codes.
- All whirlpool or Airbath[®] units require an access panel.
- Hot water supply should be 65-75% of tub capacity or greater. Always consult your local plumber for recommendations as installations will vary.
- Cut-out dimensions: Zuma recommends you wait until you have the actual unit or contact us for a template.